



S.C. ITAL-KOL S.R.L.
RO, 307395 Comuna Șag, Str. XI nr. 64, Județ Timiș, România,
Tel.: +40 256 395 200; +40 256 395 300, Fax: +40 256 395 100,
C.I.F.: RO 6470443, Nr. Înreg.Reg.Com.: J35 / 3176 / 93

CONSTRUIESTE
CORECT

Data Sheet

Ed.1 /Rev.3 | Cod F.14.00.05
Revised and amended on:
02.03.2011

PRIMER L 7012

Code 1.5.04
EC
Conformity attestation system 3

Product type: Liquid primer for treating compact nonabsorbent surfaces on which the self-levelling screed AUTOLIV is to be applied - according to SR.EN. 1504-2/2005.

Short description of product: PRIMER L 7012 primer is a white synthetic resin dispersion, having a slightly viscous appearance and being water soluble.

Areas of application: PRIMER L 7012 is used for preparing compact and nonabsorbent surfaces on which the self-levelling screed AUTOLIV is to be applied.

Technical data:	Physical form	liquid
	Colour	white
	Flammability	no
	Toxicity	no
	Density	approx. 0.9 kg / l
	pH	9
	Volatile substance content	min. 16.49%
	Specific consumption (depending on the degree of absorption of support)	0.1 – 0.2 l/m ²
	Permeability in the presence of water vapours	Class II 5 m < S _D < 50 m, where S _D = 24 m
	Capillary absorption	W = 0.021 kg ² / h ^{0.5}
	Temperature range for usage	+ 5°C – + 35°C

Instructions for use: *Application of product is carried out only by trained and skilled workers specialized in applications, in the following stages:*

PRIMER L 7012 is a primer for nonabsorbent or lightly absorbent surfaces (mosaic, floor tiles etc) on which the self-levelling screed AUTOLIV is applied (see AUTOLIV data sheet).

If a base layer is not compatible with AUTOLIV (see AUTOLIV data sheet), then, neither priming with PRIMER L 7012 will help make it compatible.

Before applying the product, the base layer should be vacuumed and clean, dust and salt free, with no non-adhesive substances (grease, bitumen, dust, gypsum, dye, old wall painting etc.); it should be resistant, compact, with no brittle parts and no cracks.

Priming is done by applying the non-diluted PRIMER L 7012, with the help of a brush, on the base layer (checked and cleaned as mentioned above) on which the self-levelling screed AUTOLIV is to be applied.

The primer shall be evenly spread on the entire area on which AUTOLIV is going to be applied.

The self-levelling screed shall be applied 24 hours after performing the priming procedure.

The surface on which the self-levelling screed is to be applied should be evenly covered with primer, should be kept clean and dust free until the application of the respective screed.

The surface should not be forcedly dried by ventilation or high temperatures.



S.C. ITAL-KOL S.R.L.
RO, 307395 Comuna Șag, Str. XI nr. 64, Județ Timiș, România,
Tel.: +40 256 395 200; +40 256 395 300, Fax: +40 256 395 100,
C.I.F.: RO 6470443, Nr. Înreg.Reg.Com.: J35 / 3176 / 93

Data Sheet

Ed.1 /Rev.3 | Cod F.14.00.05
Revised and amended on:
02.03.2011

PRIMER L 7012

Code 1.5.04
EC
Conformity attestation system 3

CONSTRUIESTE CORECT

Final recommendations:

The operation described above shall not be performed under direct sunlight, under powerful air currents (wind) or at air or base layer temperatures lower than 5°C or exceeding 35°C.

Packaging: The product is packaged in 5 l and 15 l canisters.

Storage: The product is stored for maximum 12 months in a dry place, in its original undamaged package.

Marking: Each canister is marked by being stamped, on the bottom, with the following information: date of production – four groups of figures symbolizing:
the day . the month . the year ending. the production batch number.

Warranty: The product has a 12 month warranty beginning on the date of production marked on the package; this warranty applies only for the storage conditions mentioned above.

- WARNING**
- The prepared product is alkaline.
 - During handling and transport, goggles, gloves and anti-dust masks should be worn.
 - In case the product gets accidentally into your eyes, wash immediately with lots of clean water and then quickly contact a doctor!
 - Products with damaged packaging should not be used.
 - The unused items should not be discarded into the sewerage system!

Note 1: The present data sheet accompanies each invoice or waybill which refers to the product presented in the sheet.

Note 2: It is forbidden to reproduce parts or fragments from the present data sheet.

Note 3: The present data sheet has been drawn up to properly inform the user about the presented product. The use of this sheet for other purpose than informing you about the product and preparing the technological specifications regarding application is strictly forbidden without the written consent of ITAL-KOL.

Note 4: For other additional information, which you consider you should receive or you find useful, we recommend that you contact the producer in writing, before using the product. Any producer liability regarding failures in applying the product resulted from misinterpreting the text of the present data sheet or from verbal consultancy is excluded.

Note 5: The data presented in the product data sheet and, mainly, the instructions regarding the manner and area of application of the product are based on the skills and practical experience of the person applying the product. Due to a large variety of materials, tools or working conditions which we cannot totally control or foresee or which, even if they are clearly mentioned in the product data sheet, are not correctly assessed by the person applying the product, in each case we recommend, before use, to carry out individual tests of applying the product, so that you can be sure that the product the present data sheet is describing is suitable for your respective field of application.

Any producer liability regarding failures in applying the product resulted from the causes mentioned above in this sheet is excluded, except for the event when the damages resulted only from the poor quality of the product that the present data sheet refers to.

Note 6: Depending on the evolution of the technical regulations applicable, the producer preserves the right to modify the present data sheet. For the purpose of confirming the data in the sheet, we recommend you to visit the web page: web www.italkol.ro prior to using the product